

DRAWING NO. SE090670		7		6		5		4		3		2		1																							
CATALOG NUMBERS	FIG NO.	COMMERCIAL COPPER CABLE RANGE		METRIC COPPER CABLE RANGE		"H"	"L"	INSTALLATION TOOLING						REV	DATE	DESCRIPTION	ECO	BY	C.H.K.																		
		RUN	TAP	RUN	TAP			MD6 HYTOOL™		OUR840	Y35 HYPRESS™		D	2018-04-06 00:00:00 EDT	UPDATED AS PER MARKUP	48872	YR	VS																			
								DIE INDEX NUMBER	DIE CATALOG NUMBER		NUMBER OF CRIMPS	NUMBER OF CRIMPS	DIE INDEX NUMBER	DIE CATALOG NUMBER	NUMBER OF CRIMPS																						
YC10C10	1	#12 SOL (Ø.081) TO #10 STR (Ø.116)	#12 SOL (Ø.081) TO #10 STR (Ø.116)	[3.32]² (Ø[2.06]) TO [6.82]² (Ø[2.95])	[3.32]² (Ø[2.06]) TO [6.82]² (Ø[2.95])	.37 [9.4]	.32 [8.1]	238	162	1		238	U238	1																							
YC8C8	1	#8 SOL (Ø.129) TO #8 STR (Ø.146)	#10 SOL (Ø.102) TO #8 STR (Ø.146)	[8.43]² (Ø[3.28]) TO [10.80]² (Ø[3.71])	[5.27]² (Ø[2.59]) TO [10.80]² (Ø[3.71])	.46 [12]	.50 [13]	162	162	2		162	U162	2																							
YC4C8	2	#6 SOL (Ø.162) TO #4 STR (Ø.232)	#8 SOL (Ø.129) TO #8 STR (Ø.146)	[13.3]² (Ø[4.11]) TO [21.1]² (Ø[5.89])	[8.4]² (Ø[3.24]) TO [8.4]² (Ø[3.71]) TO	.73 [19]	.62 [16]	BG OR 5/8	BG	2		BG	U-BG	1	1																						
YC4C6	2		#6 SOL (Ø.162) TO #6 STR (Ø.184)		[13.2]² (Ø[4.11]) TO [13.2]² (Ø[4.67])	.76 [19]	.57 [14]																														
YC4C4	1		#6 SOL (Ø.162) TO #4 STR (Ø.232)		[13.2]² (Ø[4.11]) TO [21.1]² (Ø[5.89])	.81 [21]	.57 [14]																														
YC2C4	2	#4 SOL (Ø.204) TO #2 STR (Ø.320)	#8 SOL (Ø.129) TO #4 STR (Ø.232)	[21.1]² (Ø[5.18]) TO [33.5]² (Ø[8.13])	[8.4]² (Ø[3.28]) TO [33.6]² (Ø[6.55])	.98 [25]	.67 [17]	C	W-C	2		C	U-C	1	1																						
YC2C2	1	#2 SOL (Ø.258) TO #2 STR (Ø.320)	#2 SOL (Ø.258) TO #2 STR (Ø.320)	[33.6]² (Ø[6.55]) TO [33.5]² (Ø[8.13])	[33.6]² (Ø[6.55]) TO [33.5]² (Ø[8.13])	1.05 [28]	.67 [17]																														
YC26C2	2	1/0 STR (Ø.373) TO	#8 SOL (Ø.129) TO #2 STR (Ø.320)	[53.3]² (Ø[9.47]) TO	[8.4]² (Ø[3.24]) TO [33.5]² (Ø[8.13])	1.30 [33]	.92 [23]	--	--	--		E OR O	U-E	3																							
YC26C26	1	2/0 STR (Ø.418)	1/0 STR (Ø.373) TO 2/0 STR (Ø.418)	[67.7]² (Ø[10.62])	[53.3]² (Ø[9.47]) TO [67.7]² (Ø[10.62])	1.35 [34]	.92 [23]	--	--	--		O	U-O	1																							
YC28C2	2	3/0 STR (Ø.470) TO 4/0 STR (Ø.528)	#6 SOL (Ø.162) TO #2 STR (Ø.320)	[85.2]² (Ø[11.94]) TO [107.2]² (Ø[13.41])	[13.3]² (Ø[4.11]) TO [33.5]² (Ø[8.13])	1.65 [42]	1.07 [27]	--	--	--		F OR D3	U-F	3																							
YC28C26	2		1/0 STR (Ø.373) TO 2/0 STR (Ø.418)		[53.3]² (Ø[9.47]) TO [67.7]² (Ø[10.62])	1.61 [41]	1.07 [27]	--	--	--																											
YC28C28	1		3/0 STR (Ø.470) TO 4/0 STR (Ø.528)		[85.2]² (Ø[11.94]) TO [107.2]² (Ø[13.41])	1.56 [40]	1.07 [27]	--	--	--																											
SELECTOR CHART		RUN CONDUCTOR													SELECTOR CHART																						
		[3.3]² SOL.	[6.8]² STR.	[8.4]² SOL.	[8.4]² STR.	[13.2]² SOL.	[13.2]² STR.	[21.1]² SOL.	[21.1]² STR.	[33.6]² SOL.	[33.5]² STR.	[53.3]² STR.	[67.7]² STR.	[85.2]² [107.2]² STR.																							
		#12 SOL.	#10 STR.	#8 SOL.	#8 STR.	#6 SOL.	#6 STR.	#4 SOL.	#4 STR.	#2 SOL.	#2 STR.	1/0 STR.	2/0 STR.	3/0 STR. 4/0 STR.																							
TAP CONDUCTOR	[3.3]² SOL.	#12 SOL.	YC10C10	YC8C8	YC4C8	YC4C6	YC2C4	YC26C2	YC28C2	[5.3]² SOL.	#10 SOL.	[6.8]² STR.	#10 STR.	[8.4]² SOL.	#8 SOL.	[8.4]² STR.	#8 STR.	[13.2]² SOL.	#6 SOL.	[13.2]² STR.	#6 STR.	[21.1]² SOL.	#4 SOL.	[21.1]² STR.	#4 STR.	[33.6]² SOL.	#2 SOL.	[33.5]² STR.	#2 STR.	[53.3]² STR.	1/0 STR.	[67.7]² STR.	2/0 STR.	[85.2]² STR.	3/0 STR.	[107.2]² STR.	4/0 STR.
	[5.3]² SOL.	#10 SOL.																																			
	[6.8]² STR.	#10 STR.																																			
	[8.4]² SOL.	#8 SOL.																																			
	[8.4]² STR.	#8 STR.	YC4C6	YC2C4	YC26C2	YC28C2	YC2C2	YC26C26	YC28C28																												
	[13.2]² SOL.	#6 SOL.																																			
	[13.2]² STR.	#6 STR.																																			
	[21.1]² SOL.	#4 SOL.																																			
	[21.1]² STR.	#4 STR.	YC4C4	YC2C4	YC26C2	YC28C2	YC2C2	YC26C26	YC28C28																												
	[33.6]² SOL.	#2 SOL.																																			
	[33.5]² STR.	#2 STR.																																			
	[53.3]² STR.	1/0 STR.																																			
[67.7]² STR.	2/0 STR.	YC26C26	YC28C28																																		
[85.2]² STR.	3/0 STR.																																				
[107.2]² STR.	4/0 STR.																																				
FIG 1		FIG 2																																			
TO ORDER BURNDY® PRODUCTS CALL		CRIMPIT™ (COPPER)																																			
UNITED STATES		ITEM NO: N/A																																			
1-800-346-4175 (LONDONERRY, NH)		CAT. NO: YC- -C- - (TABLE)																																			
CANADA:		DRAWN BY: H CIELESZ 12/05/84																																			
1-800-361-6975 (QUEBEC)		CHECKER: C.A.R. 12/10/84																																			
1-800-387-6487 (ALL OTHER PROVINCES)		DSN APPVL: R.L. 12/11/84																																			
FOR PRODUCT INFO: http://www.burndy.com		MFG APPVL: --																																			
		QA APPVL: D VARIO 07/24/97																																			
		MKT APPVL: D HAMILTON --																																			
		PROD FAM: --																																			
		PROJECT #: --																																			
		SIZE																																			
		D																																			
		SHEET 1 OF 1																																			