FLIR IRW-4C: 4in Round Infrared Inspection Window (Aluminum)

P/N: 19252-100

Copyright

© 2020, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: 19252-100
Commit: 57382
Language:
Modified: 2019-05-22
Formatted: 2020-06-17

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description
This device is a viewport which consist of a crystal "glass" window, mounted in an aluminum frame. The glass is specially formulated to allow transmission of infrared light to allow use of infrared thermal sensing equipment without opening the enclosure. This device is intended for installation in doors or walls of electrical enclosures without compromising the integrity of the enclosure.

Power system	
Voltage	Any range

Environmental data	
Environment	Indoor/outdoor type 4/12
Operating temperature range	Maximum: 260°C (500°F)
Storage temperature range	Optics, maximum: 1357°C (2474°F)

Physical data	
Size (L × W × H)	29.3 × 127 × 137 mm (1.15 × 5.01 × 5.37 in.)
Viewing aperture diameter	89 mm (3.50 in.)
Material	Optics: CaF2 (Calcium Fluoride Crystal) Body: Anodized aluminum Hardware: steel
Comments to physical data	Required hole diameter, nominal: 114.3 mm (4.5 in.) Greenlee Punch: 742BB Maximum pullout strength: 1678 kg (3700 lb.)

Lens	
Waveband	Broadband IR: short-, mid-, and longwave
Visible light spectrum	Yes

Certifications	
Certification	UL, IP67, NEMA Type 4/12, CSA

FLIR IRW-4C: 4in Round Infrared Inspection Window (Aluminum)

P/N: 19252-100

© 2020, FLIR Systems, Inc.

#19252-100; r. 57382;

Shipping information	
Packaging, type	Cardboard box
List of contents	• IR window • Case • Mounting instruction • Additional safety screw
Packaging, weight	0.46 kg (1.01 lb.)
Packaging, size	165 × 175 × 40 mm (6.50 × 6.89 × 1.58 in.)
EAN-13	4743254000742
UPC-12	845188002831
Country of origin	Estonia

Modified Date	**Modified By**
Tuesday, November 10, 2015	T&M Engineering
Description	
IRW-4C, IRW-4S	
Units	**Scale**
Inches (Millimeters)	Not to Scale

© 2015, FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means, electronic, mechanical, photocopying, recording, or otherwise, without written permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values. Products may be subject to regional market considerations. License procedures may apply. Product may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions. Diversion contrary to US law is prohibited

FLIR COMMERCIAL SYSTEMS, INC.
9 Townsend West, Nashua NH 03063 / Phone: 603.324.7800 / Fax: 603.324.7864

Declaration of Conformity

Extech Model: ***IRW 2C/2S, 3C/3S, 4C/4S***
Description: **FLIR IR Windows**
Date of Issue: ***16-May-19***

We, FLIR Commercial Systems, Inc., 9 Townsend West, Nashua, NH 03063 declare the status of the product above with regard to RoHS/REACH SVHC/PROP-65.

RoHS

RoHS Status: Not in Scope

REACH SVHC

REACH Status: Compliant

REACH Directive: 1907/2006 Article 33 (January 15, 2019)

PROP-65

Prop-65 Status: Compliant
Substance List updated November 28, 2018

The product identified above has been tested to the appropriate standards and protocols to guarantee the results as presented.

Attested to by:

Mark Sultzbach / QA Manager