# FLIR E76 24° + 42°

## P/N: 78515-1101

**Copyright**

© 2023, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

**Document identity**

Publ. No.: 78515-1101
Commit: 94076
Language:
Modified: 2023-11-08
Formatted: 2023-11-08

**Website**

http://www.flir.com

**Customer support**

http://support.flir.com

**Disclaimer**

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.




| **Imaging and optical data** | |
|---|---|
| Infrared resolution | 320 × 240 pixels |
| UltraMax (super-resolution) | Yes |
| NETD | • <30 mK, 42° @ +30°C (+86°F)<br>• <40 mK, 24° @ +30°C (+86°F) |
| Field of view | • 42° × 32°<br>• 24° × 18° |
| Minimum focus distance | • 0.15 m (0.49 ft.), 42°<br>• 0.15 m (0.49 ft.), 24° |
| Minimum focus distance with MSX | • 0.65 m (2.13 ft.), 42°<br>• 0.5 m (1.64 ft.), 24° |
| Focal length | • 10 mm (0.39 in.), 42°<br>• 17 mm (0.67 in.), 24° |
| Spatial resolution (IFOV) | • 2.41 mrad/pixel, 42°<br>• 1.31 mrad/pixel, 24° |

# FLIR E76 24° + 42°

**P/N: 78515-1101**
© 2023, FLIR Systems, Inc.
#78515-1101; r. 94076;

| **Imaging and optical data** | |
|---|---|
| Available extra lenses | • 14° (AutoCal)<br>• Dual FOV 24°/14° (service calibration required)<br>• 80° (service calibration required) |
| Lens identification | Automatic |
| f number | • 1.1, 42°<br>• 1.3, 24° |
| Image frequency | 30 Hz |
| Focus | • Continuous LDM<br>• One-shot LDM<br>• One-shot contrast<br>• Manual |
| Field of view match | Yes |
| Digital zoom | 1–4× continuous |

| **Detector data** | |
|---|---|
| Focal plane array/spectral range | Uncooled microbolometer/7.5–14 µm |
| Detector pitch | 17 µm |

| **Image presentation** | |
|---|---|
| Resolution | 640 × 480 pixels (VGA) |
| Surface brightness (cd/m$^2$) | 400 |
| Screen size | 4 in. |
| Viewing angle | 80° |
| Color depth (bits) | 24 |
| Aspect ratio | 4:3 |
| Auto-rotation | Yes |
| Touchscreen | Optically bonded PCAP |
| Display technology | IPS |
| Cover glass material | Dragontrail® |
| Programmable buttons | 1 |
| Viewfinder | No |
| Image adjustment | • Automatic<br>• Automatic maximum<br>• Automatic minimum<br>• Manual |

| **Image presentation modes** | |
|---|---|
| Infrared image | Yes |
| Visual image | Yes |
| Thermal fusion | No |
| MSX | Yes |
| Picture in Picture | Resizable and movable |
| Gallery | Yes |

**P/N: 78515-1101**
© 2023, FLIR Systems, Inc.
#78515-1101; r. 94076;

| **Measurement** | |
|---|---|
| Camera temperature range | • –20 to 120°C (–4 to 248°F)<br>• 0 to 650°C (32 to 1202°F)<br>• Optional 300 to 1000°C (572 to 1832°F) |
| Object temperature range and accuracy (for ambient temp. 15 to 35°C (59 to 95°F) | • Range –20 to 120°C (–4 to 248°F):<br>◦ –20 to 100°C (–4 to 212°F): ±2°C (±3.6°F)<br>◦ 100 to 120°C (212 to 248°F): ±2%<br>• Range 0 to 650°C (32 to 1202°F):<br>◦ 0 to 100°C (32 to 212°F): ±2°C (±3.6°F)<br>◦ 100 to 650°C (212 to 1202°F): ±2%<br>• Optional Range 300 to 1000°C (572 to 1832° F): ±2%<br>(Additional cost-P/N: T199559- High temp option) |

| **Inspection mode** | |
|---|---|
| FLIR Inspection route | Enabled in the camera |

| **Measurement analysis** | |
|---|---|
| Spotmeter | 3 in live mode |
| Area | 3 in live mode |
| Automatic hot/cold detection | Auto-maximum/minimum markers within area |
| Measurement presets | • No measurements<br>• Center spot<br>• Hot spot<br>• Cold spot<br>• User preset 1<br>• User preset 2 |
| Difference temperature | Yes |
| Reference temperature | Yes |
| Emissivity correction | Yes: variable from 0.01 to 1.0 or selected from materials list |
| Measurement corrections | Yes |
| External optics/windows correction | Yes |

| **Alarm** | |
|---|---|
| Color alarm (isotherm) | • Above<br>• Below<br>• Interval<br>• Condensation (moisture/humidity/dewpoint)<br>• Insulation |
| Measurement function alarm | Audible/visual alarms (above/below) on any selected measurement function |

**P/N: 78515-1101**
© 2023, FLIR Systems, Inc.
#78515-1101; r. 94076;

| **Set-up** | |
|---|---|
| Color palettes | • Arctic<br>• White hot<br>• Black hot<br>• Iron<br>• Lava<br>• Rainbow<br>• Rainbow HC |
| Setup commands | Local adaptation of units, language, date and time formats |
| Languages | 21 |

| **Service functions** | |
|---|---|
| Camera software update | Using USB cable or SD card |

| **Storage of images** | |
|---|---|
| Storage media | • Removable memory: SD card (8 GB)<br>• FLIR Ignite Cloud services (with Wi-Fi) |
| Time lapse (periodic image storage) | 10 seconds to 24 hours (infrared) |
| Remote control operation | Using USB cable or Wi-Fi |
| Image file format | Standard JPEG, measurement data included. Infrared-only mode |

| **Image annotations** | |
|---|---|
| Voice | 60 seconds built-in microphone and speaker (and via Bluetooth) on still images and video |
| Text | Text from predefined list or soft keyboard on touchscreen |
| Visual image annotation | Yes |
| Image sketch | Yes: on infrared images only |
| Sketch | From touchscreen |
| METERLiNK | Wireless connection (Bluetooth) to:<br>FLIR meters with METERLiNK |
| Compass | Yes |
| Laser distance meter information | Yes |
| Area measurement information | No |
| GPS | Yes: location data automatically added to every still image and the first frame in video from built-in GPS |

| **Video recording in camera** | |
|---|---|
| Radiometric infrared-video recording | RTRR (.csq) |
| Non-radiometric infrared-video recording | H.264 to memory card |
| Visual video recording | H.264 to memory card |

**P/N: 78515-1101**
© 2023, FLIR Systems, Inc.
#78515-1101; r. 94076;

| **Video streaming** | |
|---|---|
| Radiometric infrared–video streaming (compressed) | Over UVC |
| Non-radiometric video streaming (compressed: IR, MSX, visual, Picture in Picture) | • H.264 (AVC) over RTSP (Wi-Fi)<br>• MPEG4 over RTSP (Wi-Fi)<br>• MJPEG over UVC and RTSP (Wi-Fi) |
| Visual video streaming | Yes |

| **Digital camera** | |
|---|---|
| Resolution | 5 MP with LED light |
| Focus | Fixed |
| Field of view | 53° × 41° |
| Video lamp | Built-in LED light |

| **Laser pointer** | |
|---|---|
| Laser alignment | Position is automatically displayed on the infrared image |
| Laser distance meter | Activated by a dedicated button |
| Laser | Class 2, 0.05–40 m (1.6–131 ft.) ±1% of measured distance |

| **Data communication interfaces** | |
|---|---|
| Interfaces | USB 2.0, Bluetooth, Wi-Fi, DisplayPort |
| METERLiNK/Bluetooth | Communication with headset and external sensors |
| Wi-Fi | Peer to peer (*ad hoc*) or infrastructure (network) |
| Audio | Microphone and speaker for voice annotation of images |
| USB | USB Type-C: data transfer/video/power |
| USB standard | USB 2.0 High Speed |
| Video out | DisplayPort |
| Video connector type | DisplayPort over USB Type-C |
| Cloud services | FLIR Ignite Cloud services |

| **Radio** | |
|---|---|
| Operating frequency | Bluetooth + EDR/LE: 2402–2480 MHz<br>WLAN 2.4 GHz: 2412–2462 MHz<br>WLAN 5 GHz: 5150–5350 MHz (DFS: only slave mode)<br>Note that frequency band 5150–5350 MHz is for indoor use only, see national regulations. |
| RF output (EIRP) | Bluetooth + EDR/LE: < 10 dBm<br>WLAN: < 17 dBm |
| Antenna | Integrated PIFA antenna (gain: maximum 1.4 dBi) |

| **Power system** | |
|---|---|
| Battery type | Rechargeable Li-ion battery |
| Battery voltage | 3.6 V |

**P/N: 78515-1101**
© 2023, FLIR Systems, Inc.
#78515-1101; r. 94076;

| **Power system** | |
|---|---|
| Battery operating time | > 2.5 hours at 25°C (68°F) and typical use |
| Charging system | In camera (AC adapter or 12 V from a vehicle) or two-bay charger |
| Charging time (using two-bay charger) | 2.5 hours to 90% capacity with charging status indicated by LEDs |
| Charging temperature | 0°C to +45°C (+32°F to +113°F), except for the Korean market: +10°C to +45°C (+50°F to +113° F) |
| External power operation | AC adapter 90–260 V AC, 50/60 Hz, or 12 V from a vehicle (cable with standard plug—optional) |
| Power management | Automatic shut-down and sleep mode |
| Battery documents | For documents like MSDS and UN38.3 test reports/summaries, see: https://support.flir.com/resources/msds |

| **Environmental data** | |
|---|---|
| Operating temperature range | –15 to +50°C (5–122°F) |
| Storage temperature range | –40 to +70°C (–40 to +158°F) |
| Humidity (operating and storage) | IEC 60068-2-30/24 hours/95% relative humidity 25–40°C (77–104°F)/two cycles |
| EMC | • ETSI EN 301 489-1 (radio)<br>• ETSI EN 301 489-17<br>• EN 61000-6-2 (immunity)<br>• EN 61000-6-3 (emission)<br>• FCC 47 CFR part 15 B, class B (emission) |
| Radio spectrum | • ETSI EN 300 328<br>• ETSI EN 301 893<br>• FCC 47 CFR part 15 C<br>• FCC 47 CFR part 15 E |
| Encapsulation | IP 54 (IEC 60529) |
| Shock | 25*g* (IEC 60068-2-27) |
| Vibration | 2*g* (IEC 60068-2-6) |
| Drop | Designed for 2 m (6.6 ft.) |
| Safety | Camera:<br>• IEC/EN 60950-1, IEC/EN 62368-1<br>Power supply:<br>• IEC/EN 62368-1<br>• CSA/UL/KC/SAA/PSE 60950-1 |
| Declaration of conformity | See: https://support.flir.com/resources/DoC |

| **Physical data** | |
|---|---|
| Weight (including battery) | 1 kg (2.2 lb.) |
| Size (L × W × H) | 278.4 × 116.1 × 113.1 mm (11.0 × 4.6 × 4.4 in.) |
| Battery weight | 140 g (4.9 oz.) |
| Battery size (L × W × H) | 150 × 46 × 55 mm (5.9 × 1.8 × 2.2 in.) |
| Tripod mounting | UNC ¼″-20 |

**P/N: 78515-1101**
© 2023, FLIR Systems, Inc.
#78515-1101; r. 94076;

| **Physical data** | |
|---|---|
| Housing material | PCABS with TPE, magnesium |
| Color | Black |

| **Warranty and service** | |
|---|---|
| Warranty | http://www.flir.com/warranty/ |

| **Shipping information** | |
|---|---|
| Packaging, type | Cardboard box |
| Packaging, contents | • Accessory Box I:<br>  ◦ Power supply for battery charger<br>  ◦ Power supply, 15 W/3 A<br>  ◦ Printed documentation<br>  ◦ SD card (8 GB)<br>  ◦ USB 2.0 A to USB Type-C cable, 1.0 m<br>  ◦ USB Type-C to HDMI adapter, standard specification UH311<br>  ◦ USB Type-C to USB Type-C cable (USB 2.0 standard), 1.0 m<br>• Accessory box II:<br>  ◦ Accessory box III:<br>  – Front protection fastener<br>  – Hand strap bracket, left<br>  – Hand strap bracket, right<br>  – Screws<br>  – Torx T10 wrench<br>  ◦ Carabiner hook<br>  ◦ Front protection<br>  ◦ Hand strap<br>  ◦ Lanyard strap, camera<br>  ◦ Lens cap strap<br>  ◦ Wrist strap<br>• Battery (2 ea)<br>• Battery charger<br>• Extra lens, 42°<br>• FLIR Thermal Studio Starter<br>• Hard transport case<br>• Infrared camera with lens<br>• Lens cap, front<br>• Lens cap, front and rear (only for extra lenses) |
| Packaging, weight | 6.2 kg (13.7 lb.) |
| Packaging, size | 500 × 190 × 370 mm (19.7 × 7.5 × 14.6 in.) |
| EAN-13 | 4743254004634 |
| UPC-12 | 845188022631 |
| Country of origin | Estonia |

**Supplies & accessories:**


- T300587; IR lens Dual FOV, f=17/29 mm (24°/14°) with case
- T131171ACC; Remote operation button
- T300030; Option, No radio
- T911997; Tripod
- T911998; HDMI 2-port video splitter
- T300369; Mounting kit (FLIR T5xx, T8xx, Exx)
- T300768; Port adapter

**P/N: 78515-1101**
© 2023, FLIR Systems, Inc.
#78515-1101; r. 94076;

- T300493ACC; Industrial protective lens window
- T850111; Option, Dual streaming
- T130337ACC; Calibration target
- T199330ACC; Battery
- T199346ACC; Hard transport case for FLIR Exx series
- T199425ACC; Battery charger
- T199557ACC; Accessory Box II
- T199559; High temperature option, +300 to +1000°C
- T911630ACC; Power supply for camera, 15 W/3 A
- T911633ACC; Power supply for battery charger
- T911689ACC; Pouch for FLIR E-series
- T911705ACC; USB Type-C to USB Type-C cable (USB 2.0 standard), 1.0 m
- T911706ACC; Car adapter 12 V
- T911845ACC; USB Type-C to HDMI and PD adapter
- T911846ACC; USB 2.0 A to USB Type-C with Power supply
- T911940ACC; USB 2.0 A to USB Type-C cable, 1.0 m
- T300437ACC; Lens case
- T199588; IR lens, f=29 mm (14°) with case
- T199589; IR lens, f=17 mm (24°) with case
- T199590; IR lens, f=10 mm (42°) with case
- T300805; IR lens, f=5 mm (80°) with case
- T197771ACC; Bluetooth Headset
- T300244; FLIR Route Creator Plugin for FLIR Thermal Studio Pro, 1 Year Subscription
- T300439; FLIR Route Creator Plugin for FLIR Thermal Studio Pro, Perpetual license
- T300243; FLIR Thermal Studio Pro, 1 Year Subscription
- T300083; FLIR Thermal Studio Pro, Perpetual license
- T300341; FLIR Thermal Studio Standard, 1 Year Subscription
- T300258; FLIR Thermal Studio Standard, Perpetual license
- 4232535; FLIR Research Studio, Professional Edition - 1 Year Subscription (online activation)
- 4232556; FLIR Research Studio, Professional Edition - Perpetual License (online activation)
- 4232590; FLIR Research Studio, Professional Edition - Perpetual License (USB dongle)
- 4220499; FLIR Research Studio, Standard Edition - 1 Year Subscription (online activation)
- 4220500; FLIR Research Studio, Standard Edition - Perpetual License (online activation)
- 4220646; FLIR Research Studio, Standard Edition - Perpetual License (USB dongle)
- T198696; FLIR ResearchIR Max 4 (hardware sec. dev.)
- T199013; FLIR ResearchIR Max 4 (printed license key)
- T199043; FLIR ResearchIR Max 4 Upgrade (printed license key)
- 4232591; FLIR ResearchIR to Research Studio, Professional Edition - 1 Year License Upgrade

This document must not be communicated or copied completely or in part, without our permission. Any infringement will lead to legal proceedings.
FLIR SYSTEMS AB

# Exx incl. IR Lens std.





| | | | |
|---|---|---|---|
| Modified by: A. AGARDSON | Approved by: AKZE | Modified: 2023-09-29 | FLIR |
| This document does not contain any export-controlled information. | | Size: A3 | |
| Denomination: Basic dimension drawing Exx | | Scale: 1:2 | Sheet: 1(3) |
| | | Drawing No: T130127 | Rev: E |

Denna handling får ej delges annan, kopieras i sin helhet eller delar utan vårt medgivande och innehållet får ej heller bevisas med stöd av gällande lag.
FLIR SYSTEMS AB

This document must not be communicated or copied completely or in part, without our permission. Any infringement will lead to legal proceedings.
FLIR SYSTEMS AB

# Exx incl. IR Lens DFOV 17/29mm





**Weight including IR Lens DFOV 17/29mm (25°/15°):**
**approx. 1.16 kg**

| | | | |
|---|---|---|---|
| Modified by: A. AGARDSON | Approved by: AKZE | Modified: 2023-09-29 | FLIR |
| This document does not contain any export-controlled information. | | Size: A3 | |
| Denomination: Basic dimension drawing Exx | | Scale: 1:2 | Sheet: 2(3) |
| | | Drawing No: T130127 | Rev: E |

Denna handling får ej delges annan, kopieras i sin helhet eller delar utan vårt medgivande. Överträdelse härav beivras med stöd av gällande lag.
FLIR SYSTEMS AB

This document must not be communicated or copied completely or in part, without our permission. Any infringement will lead to legal proceedings.
FLIR SYSTEMS AB

# Exx incl. IR Lens 5mm




**Weight including IR Lens 5mm (80°): approx. 1.48 kg**

| | | | |
|---|---|---|---|
| Modified by: A. AGARDSON | Approved by: AKZE | Modified: 2023-09-29 | FLIR |
| This document does not contain any export-controlled information. | | Size: A3 | |
| Denomination: Basic dimension drawing Exx | | Scale: 1:2 | Sheet: 3(3) |
| | | Drawing No: T130127 | Rev: E |

Denna handling får ej delges annan, kopieras i sin helhet eller delar utan vårt medgivande. Överträdelse härav kan beivras med stöd av gällande lag.
FLIR SYSTEMS AB