In-truck charger

P/N: T198322ACC

Copyright

© 2022, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T198322ACC
Commit: 84328
Language:
Modified: 2022-03-31
Formatted: 2022-03-31

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



Power system	
Charging time	< 4 hours
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power, connector type	Screw terminal or HRS_UK60-3PT
DC operation	12/ 24 V DCnominal (11.1 - 28.0 V DC)
Power	Max 36 Watts or 3000 mA at 12 VDC (5 amps fuse)

Environmental data	
Operating temperature range	–40°C to +85°C (–40°F to +185°F)
Storage temperature range	–40°C to +85°C (–40°F to +185°F)
Relative humidity	Operational for non-condensing humidity between 5% and 95%.
EMC	• EN61000-6-3 Emission • EN61000-6-2 Immunity • FCC47CFR part 15 class B • NFPA requirements • ISO 7637-2 Road vehicles - Electrical disturbances from conduction and coupling Part 2: Electrical transient conduction along supply lines only
Encapsulation	IP 20
Bump	Operational after exposed to: 5 pulses/ in each axis/ direction (30 total) of 30g 11ms half sine profile
Vibration	Operational after exposed to: 4, 3g rms random profile. 8 hours in each axis.
Declaration of conformity	See: https://support.flir.com/resources/DoC

Physical data	
Weight	1.050 kg
Size (L × W × H)	380 mm × 180 mm × 153 mm (15 in. × 7.1 in. × 6 in.)
Material	PC / ABS
Color	Grey / black

In-truck charger

P/N: T198322ACC

© 2022, FLIR Systems, Inc.


#T198322ACC; r. 84328;


Shipping information	
List of contents	• Charger • Documentation • Card board box
Packaging, weight	3.2 kg (7.0 lb.)
Packaging, size	435 × 245 × 167 mm (17.1 × 9.6 × 6.6 in.)
EAN-13	4743254002159
UPC-12	845188011673
Country of origin	Malaysia

Compatible with the following products:

- 72203-0411; FLIR K33
- 72203-0511; FLIR K53
- 72201-0106; FLIR K45
- 72201-0206; FLIR K55
- 72202-0303; FLIR K65

This document must not be communicated or copied completely or in part, without our permission. Any infringement will lead to legal proceedings.
FLIR SYSTEMS AB





-

Konstr/Drawn P. MARCUS	Datum/Date 2013-04-08	Kontr/Check MABR	Material
Ändrad av/Modified by P. MARCUS	Ändrad/Modified 2013-04-08	Ytjämnhet/Roughness Ra µm	Ytbehandling/Surface treatment

FLIR

Där ej annat anges/Unless otherwise stated
Gen tol ISO 2768-mK
Utdrag ur/Excerpt from ISO 2768-m

0,5-6	±0,1	Hålkälsradier
(6)-30	±0,2	Fillet radii
(30)-120	±0,3	
(120)-400	±0,5	Kanter brutna
(400)-1000	±0,8	Edges broken

Benämning/Denomination

Basic dimensions
In-truck charger

Skala/Scale 1:5		Blad/Sheet 1(1)
Art.No.		Size A4
Ritn nr/Drawing No T127865		Rev A

Denna handling får ej delges annan, kopieras i sin helhet eller delar utan vårt medgivande. Överträdelse härav beivras med stöd av gällande lag.
FLIR SYSTEMS AB