In-truck charger

P/N: T199414ACC

Copyright

© 2022, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T199414ACC
Commit: 84329
Language:
Modified: 2022-03-31
Formatted: 2022-03-31

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



Power system	
Charging time	2 hours from fully depleted battery
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power, connector type	• 2–pole screw terminal (on incoming cable to DC-DC converter) • USB-A (on outgoing cable from DC-DC converter) • USB Micro-B (on in-truck charger)
DC operation	• 8–50 V DC in to DC-DC converrter • 5V DC, 3 A max. from DC-DC converter

Environmental data	
Operating temperature range	–40°C to +85°C (–40°F to +185°F)
Storage temperature range	–40°C to +85°C (–40°F to +185°F)
Relative humidity	Operational for non-condensing humidity between 5% and 95%.
EMC	• EN61000-6-3, Emission • EN61000-6-2, Immunity • FCC47CFR part 15 class B • NFPA requirements • ISO 7637-2 Road vehicles - Electrical disturbances from conduction and coupling Part 2: Electrical transient conduction along supply lines only
Bump	Operational after exposed to: 5 pulses/ in each axis/ direction (30 total) of 30g 11ms half sine profile
Vibration	Operational after exposed to: 4, 3g rms random profile. 8 hours in each axis.
Declaration of conformity	See: https://support.flir.com/resources/DoC

In-truck charger

P/N: T199414ACC

© 2022, FLIR Systems, Inc.

#T199414ACC; r. 84329;

Physical data	
Color	Black

Shipping information	
Packaging, type	Card board box
List of contents	• In-truck charger • Screws and rivets kit • USB cable • DC-DC Converter • Fuse • Documentation
EAN-13	4743254002579
UPC-12	845188013363
Country of origin	Malaysia

Compatible with the following products:

- 73701-0101; FLIR K2